

AD-A038 079

ATLANTIC RESEARCH CORP ALEXANDRIA VA
DEVELOPMENT OF HGH TEMPERATURE RESISTANT MATERIALS FOR USE IN N--ETC(U)
JAN 73 B J MACRI, F FONZI, E L OLCOTT

N00017-73-C-4306

F/G 11/4

UNCLASSIFIED

TR-PL-10124-00-2

NL

| of |
ADA038079



END

DATE
FILMED
4-77

ADA 038079



ATLANTIC RESEARCH CORPORATION

SHIRLEY MEMORIAL HIGHWAY AT EDSALL ROAD
ALEXANDRIA, VIRGINIA 22314 703-354-3400

⑥ DEVELOPMENT OF HIGH TEMPERATURE RESISTANT
MATERIALS FOR USE IN NAVAL ORDNANCE.

Contract No. N00017-73-C-4306

Second Quarterly Report

no. 2, 1 Nov 72 -
5 Jan 73,

Submitted to:

Naval Ordnance Systems Command
Department of the Navy
Washington, D. C. 20360

Prepared by:

ATLANTIC RESEARCH CORPORATION
Shirley Highway and Edsall Road
Alexandria, Virginia 22314

⑩ Bruno J. Macri,
Frank Fonzi
Eugene L. Olcott

Period Covered:

1 November 1972 to 5 January 1973


⑪ 18 Jan 73
January 18, 1973

⑫ 8 p.m.

Approved for public release;
Distribution Unlimited

⑭ TR-PL-10124-00-2

AJ NO. _____
DDC FILE COPY



045550

609

Letter on file

A

1.0 INTRODUCTION

During the previous phases of this program, the potential of the Pyrostrand® concept was observed to be worthy of continued development. Pyrostrand is a graphite composite produced by winding a filamentary carbon or graphite reinforcement on a mandrel in a furnace at 3,650°F, while continuously depositing a matrix of pyrolytic graphite. Additional features of this concept include: (1) the simultaneous deposition of carbides (when desired) to modify the matrix structure, (2) the use of filamentary materials of various textile configurations and mechanical properties and (3) the control of reinforcement placement and content for increased strength and greater erosion resistance in very-high-temperature environments.

The pyrolytic graphite matrix has inherently high resistance to erosion under rocket motor firing conditions. A disadvantage of the material is its tendency to delaminate at moderate or excessive thicknesses. This delamination tendency can be reduced by causing the pyrolytic graphite to grow from surfaces other than the substrate, a filamentary reinforcement for example. The high performance graphite yarns have a very high strength/density ratio and thereby offer the potential for producing composites with a significant degree of reinforcement. In contrast to most materials,

the strength of both major components of these composites increases with temperature up to near the sublimation temperature of graphite (6,600°F).

Past progress has been limited by a small furnace and a small capacity for handling the filamentary material. The results were sufficiently promising to indicate that further work should be conducted to scale up the equipment for the production of larger pieces and to solve the problems identified in earlier studies. The most important of these problems were: (1) voids inside yarn and at yarn crossing points, (2) growth of pyrolytic graphite on broken filament ends, which prevented smooth winding in subsequent layers and (3) insufficient yarn handling capability to prepare thick specimens.

For advanced propulsion systems throat inserts may be required in sizes up to 12.5 inches throat diameter. Assuming an outside diameter of 14 inches, a furnace diameter of approximately 16 inches is indicated, resulting in a fourfold cross sectional area extrapolation. Transition to a fabrication system of this size and demonstration of 7-inch nozzle fabrication and test are the objectives of this program.

A discussion of the program approach was presented in Reference 1. Work accomplished during the two month report period is described below.

2.0

WORK ACCOMPLISHED

Most of the work accomplished related to the procurement of equipment required for the size scale-up. Company funds were received for the purchase of this equipment.

A new atmosphere control chamber and induction coil have been ordered with a scheduled delivery in late February. An objective in both the control chamber and furnace design was to provide a system suitable for transition to production operation, if required, without significant changes.

The new equipment will consist of three major sections: (1) the vacuum tank to contain the controlled atmosphere, (2) the induction coil and (3) the furnace assembly.

The vacuum tank was designed to be 72 inches in diameter and 60 inches high. It will be constructed from 304 stainless steel in two sections, split horizontally, and provided with flanges for vacuum sealing. Operations under either vacuum or differential pressure conditions will be possible. A rupture disk system will be installed with a low blow-out rating. This will insure an adequate pressure release in the event of an inadvertent overpressure.

During routine operations the lower half of the tank will remain fixed in place and only the upper tank lid removed for access to the furnace area.

A sealed yarn box will be constructed and positioned on a flange outside of the tank. The yarn box will contain the same pressure conditions that will exist in the furnace, and also will permit visual observation of the operations within the box.

All utility connections will pass through the lower tank wall.

A copper induction coil 33 inches in diameter and 41 inches high is being fabricated. It will be insulated by wrapping with fiberglass tape and impregnated with high temperature resistant varnish. Cooling coils will be located above and below the induction coil to provide for temperature gradients in the outer furnace area. The inside of the coil will be lined with alternate layers of refractory cement and fiberglass cloth. A cooling plate on the bottom of the furnace will be bolted to the coil and support the susceptor, work load and lampblack insulation. It will be possible to lift the entire furnace out of the bottom tank section. There will, however, be a certain amount of connections to be taken apart to remove the furnace.

Furnace support systems such as gas dryers, control panels, nitrogen deluge and a closed water cooling system are being pursued.

Additional operations for future considerations are as follows:

1. An automatic control device for monitoring the yarn tension.
2. Utilization of laser beam illumination to obtain a visual check on the winding operation.

3.0 FUTURE WORK

During the next three month period all fabrication components should be received and initial check-out should be underway.

LIST OF REFERENCES

1. "Development of High Temperature Resistant Materials for Use In Naval Ordnance," First Quarterly Report prepared by Atlantic Research Corporation under Contract No. N00017-73-C-4306 for Naval Ordnance Systems Command, November 15, 1972.

Security Classification

DOCUMENT CONTROL DATA - R & D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author)		2a. REPORT SECURITY CLASSIFICATION	
Atlantic Research		UNCLASSIFIED	
		2b. GROUP	
3. REPORT TITLE			
Development of High Temperature Resistant Materials for Use in Naval Ordnance			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)			
Second Quarterly Report - 1 November 1972 to 5 January 1973			
5. AUTHOR(S) (First name, middle initial, last name)			
Bruno J. Macri; Frank Fonzi; Eugene L. Olcott			
6. REPORT DATE		7a. TOTAL NO. OF PAGES	7b. NO. OF REFS
January 18, 1973		6	1
8a. CONTRACT OR GRANT NO.		9a. ORIGINATOR'S REPORT NUMBER(S)	
N0017-73-C-4306		TR-PL-10124-00-0	
b. PROJECT NO.		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
42-5566			
c.			
d.			
10. DISTRIBUTION STATEMENT This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with the approval of the Commander, Naval Ordnance Systems Command.			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY	
		Naval Ordnance Systems Command	
13. ABSTRACT			
<p>Work continued on process scale-up to permit the fabrication of filament reinforced graphite composites in sizes up to 16-inch outer diameter. The design of the outer vacuum container was completed and the container was ordered. The design of the furnace induction coil was completed, and the coil was placed on order. The required scale-up components should be available during the next report period.</p> <p>The scale-up version includes several desirable features, not available in previous fabrication equipment. These include external filament storage to permit observation of the filament feed system during fabrication, suitable view ports to permit laser beam illumination and visual observation of the fabrication process inside the furnace, and various arrangements to permit the use of the equipment for subsequent production requirements.</p>			

DD FORM 1473
1 NOV 65

Security Classification

Security Classification

14	KEY WORDS	LINK A		LINK B		LINK C	
		ROLE	WT	ROLE	WT	ROLE	WT
	<p>Graphite Composites Pyrolytic Graphite Graphite Yarn High-Temperature Materials</p>						

Contract No. N00017-73-C-4306
Distribution

Commander Naval Ordnance Systems Command Attention Code ORD-0333 (2) Code ORD-0632 (2) Washington, DC 20360	Commander U. S. Naval Ordnance Laboratory Attention Library White Oak Silver Spring, MD 20910 (1)	Commander U. S. Naval Ordnance Laboratory Attention Code 234 White Oak Silver Spring, MD 20910 (1)
Army Ballistic Res. Labs. Attention AMXBR-1 Aberdeen Proving Ground, MD 21005 (1)	Jet Propulsion Laboratory Attention Chief, Reports Group 4800 Oak Grove Drive Pasadena, CA 91103 (1)	Commander U. S. Naval Weapons Center Attention Code 753 China Lake, CA 93555 (2)
U.S. Army Missile Command Attn: Chief, Documentation Section (4) Redstone Scientific Info. Center Redstone Arsenal, AL 35809	Commanding Officer U. S. Naval Ordnance Station Attention Res. & Development Dept. Indian Head, MD 20640 (1)	National Aeronautics & Space Adm. Attention Code RPS Washington, DC 20546 (1)
Allegheny Ballistics Laboratory (1) Attention Tech. Library Hercules, Inc. Cumberland, MD 21502	Defense Ceramic Info. Center Battelle Memorial Institute Attention Manager of Tech. Info. 505 King Avenue Columbus, OH 43201 (1)	National Aeronautics & Space Adm. Lewis Research Center Attention Library 21000 Brookpark Road Cleveland, OH 44135 (1)
Defense Documentation Center (TSR) Cameron Station - Bldg. 5 Alexandria, VA 22314 Via: Commander Code ORD-0632 Naval Ordnance Systems Command (12)	Department of the Navy Naval Air Systems Command Attention AIR-50231B (1) AIR-5367 (1) Washington, DC 20360	National Aeronautics & Space Adm. George C. Marshall Space Flight Ct. Attention Librarian Huntsville, AL 35812 (1)
Defense Metals Info. Center Battelle Memorial Institute Attention Reports Library (CPIA) 505 King Avenue Columbus, OH 43201 (1)	Chemical Propulsion Info. Agency Applied Physics Laboratory Johns Hopkins University 8621 Georgia Avenue Silver Spring, MD 20910 (3)	Rocket Propulsion Laboratories Air Force Systems Command Attention Code MK Edwards, CA 93523 (1)
National Aeronautics & Space Administration Attention Office of Tech. Info. & Educational Programs, Code ETL Washington, DC 20546 (1)	Commanding Officer Army Mechanics & Materials Res.Ctr. Attention Tech. Info. Section Watertown, MA 02172 (1)	Applied Physics Laboratory Johns Hopkins University Attention Doc. Librarian 8621 Georgia Avenue Silver Spring, MD 20910 (1)
Director Strategic Systems Project Office Department of the Navy Attn: Mr. R. Kinert, SP-273(1) (1) Dr. J. Kincaid, SP-20 (1) Technical Library (1) Washington, DC 20360	Battelle Memorial Inst. Columbus Laboratories Attn: Report Library (RUT/O) 505 King Avenue Columbus, OH 43201 (1)	
Wright-Patterson AFB, OH 45433 Attention AFML (MAAE) (1) AFML (MAAM) (1) AFML (MAMC) (1) AFML (MANC) (1)	Battelle Memorial Inst. Columbus Laboratories Attention DMIC 505 King Avenue Columbus, OH 43201 (1)	
Aerospace Corporation Attention Mr. J. Baetz P.O. Box 95085 Los Angeles, CA 90045 (1)	Lockheed Missiles & Space Company Attention Mr. J. Huizinga P.O. Box 504, Bldg. 154 Sunnyvale, CA 94088 (1)	
Scientific and Tech. Info. Facility Attn: NASA Representative P.O. Box 33 College Park, MD 20740 (2)		
NASA Lewis Research Center Attention Mr. Roy F. Lark Mail Stop 49-1 21000 Brookpark Road Cleveland, OH 44135 (1)		
AFML/LNC Attention Mr. D. L. Schmidt Wright-Patterson AFB, OH 45433 (1)		
Sandia Corporation Attn: Tech. Library (3421-1) (1) Mr. H. Stoller (1) P.O. Box 5800 Albuquerque, NM 87155		